



李聯記五金有限公司
LEE'S METAL COMPANY LIMITED

(KD) 304/316L 不銹鋼水喉通 Stainless Steel Pipe



產地 Place of Origin: 中國 China

PIPE SCHEDULE (ASTM API STANDARD)							
Nominal pipe size (mm/inch)		OD (mm)	10s	40s	40	80s	車牙厚度 Minimum Wall Thickness for Threading (mm)
DN6	1/8"	10.3	1.24	1.73	1.73	2.41	
DN8	1/4"	13.7	1.55	2.24	2.24	3.02	2.00
DN10	3/8"	17.1	1.65	2.31	2.31	3.2	2.00
DN15	1/2"	21.3	2.11	2.77	2.77	3.73	2.80
DN20	3/4"	26.7	2.11	2.87	2.87	3.91	2.90
DN25	1"	33.4	2.77	3.38	3.38	4.55	3.30
DN32	1-1/4"	42.2	2.77	3.56	3.56	4.85	3.50
DN40	1-1/2"	48.3	2.77	3.56	3.56	5.08	3.50
DN50	2"	60.3	2.77	3.91	3.91	5.54	3.50
DN65	2-1/2"	73.0	3.05	5.16	5.16	7.01	4.00
DN80	3"	88.9	3.05	5.49	5.49	7.62	4.00
DN100	4"	114.3	3.05	6.02	6.02	8.56	4.00
DN125	5"	141.3	3.4	6.55	6.55	9.53	
DN150	6"	168.3	3.4	7.11	7.11	10.97	
DN200	8"	219.1	3.76	8.18	8.18	12.7	
DN250	10"	273.1	4.19	9.27	9.27	12.7	
DN300	12"	323.9	4.57	9.52	10.31	12.7	
DN350	14"	355.6	4.78		11.13		
DN400	16"	406.4	4.78		12.70		
DN450	18"	457.2	4.78		14.27		
DN500	20"	508.0	5.54		15.09		
DN550	22"	558.8	5.54		-	Wall Thickness = mm 10s, 40s, 40, 80s - ANSI B36.19	
DN600	24"	609.6	6.35		17.48		

根據水務署要求，不銹鋼喉配件（只涵蓋溝槽式、壓式及壓合式的三通接頭、彎頭、異徑管及接合件，不包括上牙配件，及燒焊配件）需要水紙

水務署(何先生) 2294 2724